

HIGH SPEED PASS THROUGH DRYER

GH-S120T
GH-S175T



Features and Benefits

- Two doors pass-thru design for connecting to tunnel washer system or to be used individually
- PLC control up to 99 drying programs editable control up to 8 dryers simultaneously
- Steam heater resists up to 1Mpa steam pressure and large heat exchange surface result in speedy drying cycle and low consumption
- Cool down bypass system reduce minimize heat loss and fast cool down
- Heat recirculation system controlled by computer improve drying efficiency and accurate temperature control
- Large unloading door opening and tilting design provides quick and efficient unloading
- Stainless steel inner basket design for easy dismantle, cleaning or replacement
- Bearings of inner basket installed in heated insulated area prolong working lifespan
- Frequency inverter driven motor with synchronizing belt system maintain reliable drive mechanism
- Dynamic balanced fan impeller ensure smooth, low vibration and quiet operation
- Can be connected to centralized automatic lint collector system reduce daily maintenance

Quality
Reliability
Performance

TECHNICAL SPECIFICATIONS

MODEL	GH-S120T	GH-S175T
Rated Capacity	120kg	175kg
POWER		
Total Power	15kw	28kw
CONNECTION		
Compressed Air Pressure	0.65Mpa	0.65Mpa
Compressed Air Consumption	900L/h	1270L/h
Compressed Air Connection	DN12	DN12
Steam Pressure	1.0Mpa	1.0Mpa
Steam Consumption	350kg/h	500kg/h
Steam Connection	DN40	DN50
Exhaust Flowrate	4,000-13,100m ³ /h	5,800-19,000m ³ /h
Exhaust Connection	DN400	DN500
DIMENSION		
Width	2050mm	2380mm
Depth	3040mm	3390mm
Height	4200mm	4600mm
Weight	3,500kg	4,500kg

For products improvement purpose, we reserve the rights to change the specification without notice

Presented by **ONE LAUNDRY MACHINERY CO. LTD.**

Address: No.2597, Puwei Highway, Fengxian District, Shanghai, 201402 China

Tel: 86-21-57407226 Fax: 86-21-57401206 (Hotline 86-13918704075, 60-147462636)

Website: www.onelaundry.com Email: info@onelaundry.com