

## CLEAN ROOM WASHER EXTRACTOR

**CJW15** 

CJW30

CJW50

CJW70

**CJW100** 



## **Features and Benefits**

- Single door front load design for lower specification clean room application
- Parts in contact with water made of SS304 stainless steel
- Frequency inverter drive allows variable speed setting
- Heavy duty spring suspension system with shock absorbers
- User friendly programmable computer in English
- Standard cold and hot water inlet valves and one drain valve
- Direct steam injection heating
- Large stainless steel loading door
- Viton flaps cover between outer drum and front panel minimize air contamination
- Automatic soapbox compartments\*1
- Safety door switch
- Out of balance switch for machine protection
- Long lasting stainless steel panels

MODEL	CJW15	CJW30	CJW50	CJW70	CJW100
Rated Capacity	15kg	30kg	50kg	70kg	100kg
Basket Volume	161L	320L	563L	709L	1012L
Basket Diameter	Ø640mm	Ø902mm	Ø1067mm	Ø1090mm	Ø1210mm
Basket Depth	500mm	500mm	630mm	760mm	880mm
Power					
Motor	1.5kw	4kw	5.5kw	7.5kw	7.5kw
Inverter	1.5kw	5.5kw	7.5kw	11kw	11kw
Electric Heater*1	13.5kw	21kw	42kw	48kw	Request
High Extract (Maximum)	300G	300G	300G	300G	300G
Dimension					
Width	930mm	1480mm	1560mm	1590mm	1700mm
Depth	1030mm	1350mm	1580mm	1930mm	1990mm
Height	1450mm	1850mm	1900mm	2000mm	1970mm
Weight					
Net weight	600kg	1650kg	2250kg	2850kg	3200kg
Connections					
Cold Water	DN25	DN40	DN40	DN40	DN40
Hot Water	DN25	DN40	DN40	DN40	DN40
Drain	DN65	DN95	DN95	DN140	DN140
Steam*2	DN20	DN25	DN25	DN25	DN25
Compressed Air	Ø8mm	Ø8mm	Ø8mm	Ø8mm	Ø8mm

For products improvement purpose, we reserve the rights to change the specification without notice

Address: No.2597, Puwei Highway, Fengxian District, Shanghai, 201402 China Tel: 86-21-57407226 Fax: 86-21-57401206 (Hotline 86-13918704075, 60-147462636)

Website: www.onelaundry.com Email: info@onelaundry.com